







IIYAMA TF6538UHSC-B1AG

TECHNICAL DETAILS

Diagonal (in) 65 Panel IPS Touch points 50 Standard UHD 4K Resolution (px×px) 3840x2160 Width of viewable area (mm) 1430.9 Height of viewable area (mm) 806 Upper / lower bezel size (mm) 49.75 / 49.75 Left / right bezel size (mm) 49.8 / 49.8 Screen aspect ratio 16.9 Max. brightness (cd/m²) 500 Viewing angles (h/v; °) 178/178 Connectors 1 x VGA (Input, 15-pin D-Sub) Connectors 1 x IR (3.5mm jack) Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 2 x HDMI (Input) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm) 1530.4 Height without stand (mm) 905.6		
Touch points 50 Standard UHD 4K Resolution (pxxpx) 3840x2160 Width of viewable area (mm) 1430.9 Height of viewable area (mm) 806 Upper / lower bezel size (mm) 49.75/49.75 Left / right bezel size (mm) 49.8/49.8 Screen aspect ratio 16:9 Max. brightness (cd/m²) 500 Viewing angles (h/v; °) 178/178 Connectors 1 x VGA (Input, 15-pin D-Sub) Connectors 1 x USB-B Connectors 1 x IR (3.5mm jack) Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm) 1530.4	Diagonal (in)	65
Standard UHD 4K Resolution (pxxpx) 3840x2160 Width of viewable area (mm) 1430.9 Height of viewable area (mm) 806 Upper / lower bezel size (mm) 49.75 / 49.75 Left / right bezel size (mm) 49.8 / 49.8 Screen aspect ratio 16.9 Max. brightness (cd/m²) 500 Viewing angles (h/v; °) 178/178 Connectors 1 x USB-B Connectors 1 x USB-B Connectors 1 x IR (3.5mm jack) Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm) 1530.4	Panel	IPS
Resolution (px×px) 3840x2160 Width of viewable area (mm) 1430.9 Height of viewable area (mm) 806 Upper / lower bezel size (mm) 49.75 / 49.75 Left / right bezel size (mm) 49.8 / 49.8 Screen aspect ratio 16:9 Max. brightness (cd/m³) 500 Viewing angles (h/v; °) 178/178 Connectors 1 x VGA (Input, 15-pin D-Sub) Connectors 1 x USB-B Connectors 1 x IR (3.5mm jack) Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm) 1530.4	Touch points	50
Width of viewable area (mm)1430.9Height of viewable area (mm)806Upper / lower bezel size (mm)49.75 / 49.75Left / right bezel size (mm)49.8 / 49.8Screen aspect ratio16:9Max. brightness (cd/m²)500Viewing angles (h/v; °)178/178Connectors1 x VGA (Input, 15-pin D-Sub)Connectors1 x USB-BConnectors2 x Audio (Input/output, 3.5mm jack)Connectors2 x HDMI (Input)Connectors1 x RS-232C (9-pin D-Sub)Connectors1 x DVI-D (Input, 24+1-pin D-Sub)Connectors1 x Ethernet (RJ45)Connectors1 x DisplayPort (Input)Typical power consumption (W)145Width without stand (mm)1530.4	Standard	UHD 4K
Height of viewable area (mm) 49.75 / 49.75 Left / right bezel size (mm) 49.8 / 49.8 Screen aspect ratio 16:9 Max. brightness (cd/m²) 500 Viewing angles (h/v; °) 178/178 Connectors 1 x VGA (Input, 15-pin D-Sub) Connectors 1 x IR (3.5mm jack) Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm) 1530.4	Resolution (px×px)	3840x2160
Upper / lower bezel size (mm) 49.75 / 49.75 Left / right bezel size (mm) 49.8 / 49.8 Screen aspect ratio 16:9 Max. brightness (cd/m²) 500 Viewing angles (h/v; °) 178/178 Connectors 1x VGA (Input, 15-pin D-Sub) Connectors 1x IR (3.5mm jack) Connectors 2x Audio (Input/output, 3.5mm jack) Connectors 2x HDMI (Input) Connectors 1x RS-232C (9-pin D-Sub) Connectors 1x Ethernet (RJ45) Connectors 1x Ethernet (RJ45) Connectors 1x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm) 1530.4	Width of viewable area (mm)	1430.9
Left / right bezel size (mm) Screen aspect ratio 16:9 Max. brightness (cd/m²) Viewing angles (h/v; °) 178/178 Connectors 1x VGA (Input, 15-pin D-Sub) Connectors 1x IR (3.5mm jack) Connectors 2x Audio (Input/output, 3.5mm jack) Connectors 2x HDMI (Input) Connectors 1x RS-232C (9-pin D-Sub) Connectors 1x Ethernet (RJ45) Connectors 1x DisplayPort (Input) Typical power consumption (W) 1530.4	Height of viewable area (mm)	806
Screen aspect ratio 16:9 Max. brightness (cd/m²) 500 Viewing angles (h/v; °) 178/178 Connectors 1x VGA (Input, 15-pin D-Sub) Connectors 1x IR (3.5mm jack) Connectors 2x Audio (Input/output, 3.5mm jack) Connectors 2x HDMI (Input) Connectors 1x RS-232C (9-pin D-Sub) Connectors 1x DVI-D (Input, 24+1-pin D-Sub) Connectors 1x Ethernet (RJ45) Connectors 1x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm) 1530.4	Upper / lower bezel size (mm)	49.75 / 49.75
Max. brightness (cd/m²) Viewing angles (h/v; °) 178/178 Connectors 1 x VGA (Input, 15-pin D-Sub) Connectors 1 x IR (3.5mm jack) Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 2 x HDMI (Input) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm)	Left / right bezel size (mm)	49.8 / 49.8
Viewing angles (h/v; °) Connectors 1 x VGA (Input, 15-pin D-Sub) Connectors 1 x USB-B Connectors 1 x IR (3.5mm jack) Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 2 x HDMI (Input) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm)	Screen aspect ratio	16:9
Connectors 1x VGA (Input, 15-pin D-Sub) Connectors 1x IR (3.5mm jack) Connectors 2x Audio (Input/output, 3.5mm jack) Connectors 2x HDMI (Input) Connectors 1x RS-232C (9-pin D-Sub) Connectors 1x DVI-D (Input, 24+1-pin D-Sub) Connectors 1x Ethernet (RJ45) Connectors 1x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm) 1530.4	Max. brightness (cd/m²)	500
Connectors 1x USB-B Connectors 1x IR (3.5mm jack) Connectors 2x Audio (Input/output, 3.5mm jack) Connectors 2x HDMI (Input) Connectors 1x RS-232C (9-pin D-Sub) Connectors 1x DVI-D (Input, 24+1-pin D-Sub) Connectors 1x Ethernet (RJ45) Connectors 1x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm) 1530.4	Viewing angles (h/v; °)	178/178
Connectors 1 x IR (3.5mm jack) Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 2 x HDMI (Input) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm) 1530.4	Connectors	1 x VGA (Input, 15-pin D-Sub)
Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 2 x HDMI (Input) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm) 1530.4	Connectors	1 x USB-B
Connectors 2 x HDMI (Input) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm) 1530.4	Connectors	1 x IR (3.5mm jack)
Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm) 1530.4	Connectors	2 x Audio (Input/output, 3.5mm jack)
Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm) 1530.4	Connectors	2 x HDMI (Input)
Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm) 1530.4	Connectors	1 x RS-232C (9-pin D-Sub)
Connectors 1 x DisplayPort (Input) Typical power consumption (W) 145 Width without stand (mm) 1530.4	Connectors	1 x DVI-D (Input, 24+1-pin D-Sub)
Typical power consumption (W) 145 Width without stand (mm) 1530.4	Connectors	1 x Ethernet (RJ45)
Width without stand (mm) 1530.4	Connectors	1 x DisplayPort (Input)
	Typical power consumption (W)	145
Height without stand (mm) 905.6	Width without stand (mm)	1530.4
	Height without stand (mm)	905.6







Depth without stand (mm)	67.6
Net weight (kg)	59.8
Set contains	Vogel's PFW 4700 wall mount
Set contains	Remote control
Set contains	Power cord

PRODUCT DESCRIPTION

SQM Rental House recommends you TF6538UHSC-B1AG - a 65-inch liyama open-frame monitor that offers phenomenal UHD 4K native resolution (3840x2160) and 50 multi-touch points. The monitor uses a high-quality IPS panel and a 5-millimeter anti-reflective coating with 178°/178° viewing angles, thanks to which the refraction of light is eliminated - perfect image quality will now be visible from any position.

liyama uses capacitive touch technology, and the TF6538UHSC-B1AG offers up to 50 points that respond to touch through stylus, latex glove and finger. The touch operates on the Plug & Play principle, is HID compatible and requires the Windows or Linux operating system. Apple products require a driver that supports one touchpoint.

The model has four digital signal inputs (2 HDMI, DVI-D and DisplayPort connectors), analog VGA port and control connectors. The monitor has two built-in 8W speakers. Iiyama works great in both horizontal and portrait positions. It also has VESA-compliant mounts (600x400mm), thanks to which the screen can be hung on the wall.

TF6538UHSC-B1AG is a monitor highly resistant to adverse conditions - the level of protection against dust and water is IP54 (on the front), and the housing made of metal ensures solidity. The monitor has a built-in kiosk mode that blocks the access of important data to unauthorized persons. The great parameters of the liyama TF6538UHSC monitor ensure that it's a perfect option as an interactive information kiosk in shopping malls and other digital signage solutions for 24/7.

Product link:

https://rentalhouse.sqm.eu/gb/touch-monitors/1001-iiyama-tf6538uhsc-b1ag.html