



GUIDETOURL AT-T1

TECHNICAL DETAILS

Device type	Transmitter
Working range (m)	90
Operating frequency (MHz)	UHF
Width (mm)	50
Height (mm)	65
Depth (mm)	17
Net weight (kg)	0.048

PRODUCT DESCRIPTION

SQM Multimedia Support presents an AT-T1 digital transmitter from the Polish brand GuideTour. The device with a large operating range (approx. 90 meters) and a very stable sound signal transmission is powered by a built-in lithium-ion battery that allows for about 15 hours of continuous use.

AT-T1 is turned on by sliding the side switch. On the display, the user is informed about the battery status, transmission channel or volume level. The last two parameters can be changed/selected by the use of the buttons located under the display.

The GuideTour AT-T1 transmitter offers 19 transmission channels at various radio frequencies and four sensitivity levels (1-4) - the higher the parameter, the higher the volume. It is possible to set the zero level, which mutes the microphone. The device has a frequency stability of $\pm 0.005\%$, a signal strength of 10mW and a frequency spacing of 75kHz.

A mini-jack (3.5mm) connector allows you to connect a microphone to the transmitter. The compact GuideTour AT-T1 is perfect for conferences and multimedia events.

Product link:

<https://rentalhouse.sqm.eu/gb/accessories/1017-guidetour-at-t1.html>