

PRODUCT NAME

IIYAMA TF5538UHSC-B1AG

DESCRIPTION

Iiyama TF5538UHSC-B1AG is a 55-inch open-frame touch monitor. The device guarantees a phenomenal image in native 4K resolution (3840x2160), 12 touch points in capacitive technology and a 5-mm anti-glare coating, thanks to which the presented content is visible in any lighting - without reflections and with perfectly visible details.

The great quality image is complemented by a very sensitive touch - it responds to a stylus, latex glove, and finger touches. The touch is HID compatible and is simple to configure with Windows and Linux OS' (Apple products require a driver that supports one touchpoint).

In addition to the fantastic image parameters that are displayed on the high-quality IPS matrix, and very accurate touch technology, the TF5538UHSC offers four digital signal inputs (one DVI-D connector, DisplayPort and 2 HDMI connectors), an analog VGA port and control connectors. Two built-in 8W speakers are responsible for the sound. The screen is adapted to work both in a horizontal and vertical position. Mounts with VESA compliance (600x400mm) allow you to easily hang the device on the wall.

Available in SQM Rental House TF5538UHSC-B1AG is a monitor ideally suited to work 24/7 in the form of an interactive information kiosk in shopping malls - high reliability of touch, great image parameters, resistance to dust and water (IP54), metal housing, or Kiosk mode that blocks access to data to

PRODUCT NAME

IIYAMA TF5538UHSC-B1AG

DESCRIPTION (CONTINUED)

unauthorized persons - these are just a few features that reinforce this belief.

SPECIFICATIONS

Panel	IPS
Diagonal (in)	55
Standard	UHD 4K
Resolution (px×px)	3840x2160
Width of viewable area (mm)	1209.6
Touch points	12
Upper / lower bezel size (mm)	42.55 / 42.55
Height of viewable area (mm)	680.4
Screen aspect ratio	16:9
Left / right bezel size (mm)	42.45 / 42.45
Viewing angles (h/v; °)	178/178
Max. brightness (cd/m²)	500
Width without stand (mm)	1294.5
Height without stand (mm)	765.5
Depth without stand (mm)	68
Typical power consumption (W)	120
Set contains	Power cord
Set contains	Edbak PWB1 wall mount
Set contains	Remote control

SPECIFICATIONS

Connectors	2 x HDMI (Input)
Connectors	1 x RS-232C (9-pin D-Sub)
Connectors	1 x DVI-D (Input, 24+1-pin D-Sub)
Connectors	1 x IR (3.5mm jack)
Connectors	1 x DisplayPort (Input)
Connectors	1 x VGA (Input, 15-pin D-Sub)
Connectors	1 x USB-B
Connectors	2 x 3.5mm jack (Audio input/output)
Connectors	1 x Ethernet (RJ45)
Net weight (kg)	41