



## HYUNDAI D405MLI

### TECHNICAL DETAILS

Diagonal (in)	40
Panel	PVA
Touch points	2
Standard	Full HD
Resolution (px×px)	1920x1080
Screen aspect ratio	16:9
Max. brightness (cd/m²)	450
Viewing angles (h/v; °)	178/178
Connectors	2 x RCA (Audio output)
Connectors	2 x RCA (Composite audio input)
Connectors	2 x HDMI (Input/output, DVI)
Connectors	1 x 3.5mm jack
Connectors	2 x RCA (Component audio input)
Connectors	2 x BNC (Input/output, Composite)
Connectors	2 x RS-232C (Input/output, 9-pin D-Sub)
Connectors	1 x 3.5mm jack (Audio input)
Connectors	6 x BNC (Input/output, Component)
Connectors	2 x VGA (Input/output, 15-pin D-Sub)
Max. power consumption (W)	200
Width without stand (mm)	985.4
Height without stand (mm)	576.4
Depth without stand (mm)	129.7
Net weight (kg)	19
Set contains	Remote control

Set contains

Power cord

## PRODUCT DESCRIPTION

The 40-inch Hyundai D405MLI is an industrial touch TV that uses a PVA panel and supports 1920x1080 resolution at 450 nits brightness. It also has great viewing angles at 178 degrees both horizontally and vertically.

The D405MLI uses a multi-touch IR module with 2 touch points - the infrared transmitters are located along the entire length of the monitor. The device is characterized by high reliability and a very resistant touch, thanks to the anti-reflective coating of tempered glass with a thickness of just 5mm. The user has at his disposal inter alia one DVI (on HDMI connector) digital input and analog VGA.

Hyundai D405MLI works great both in a standard horizontal position and in portrait mode (vertical orientation). D405MLI can also be wall-mounted (thanks to VESA mounts at 400x200mm spacing). The device is ideally suited to professional, interactive applications in commerce that require reliable equipment for continuous operation.

SQM Multimedia Support invites you to check product availability on the selected date!

Product link:

<https://rentalhouse.sqm.eu/gb/touch-monitors/131-hyundai-d405mli.html>