





PRODUCT NAME

KALI AUDIO LP-6

DESCRIPTION

The LP-6 is an active two-way studio monitor by Kali Audio that features a 6.5-inch dual-layer woofer and a 1-inch soft-dome tweeter. The Kali Audio LP-6 has an integrated class-D amplifier and the total power is equal to 80W (40W per tweeter and 40W per woofer). The frequency response (at -10dB) is between 39 and 25000 Hz.

Above all, the LP-6 monitor is characterized by clear, undamped, and unamplified sound - all thanks to its very precise frequency response. This is not the only advantage of the LP-6 - this monitor also features low noise from the front bass reflex port, high dynamic range, low distortion, and excellent bass power.

The Kali Audio LP-6 is also distinguished by its ability to adapt perfectly to the acoustics of your chosen room - all thanks to Boundary EQ Control. The LP-6 will sound perfect, no matter the environment.

Available from SQM Rental House, the Kali Audio LP-6 studio monitor features an unbalanced RCA input (with -10dB sensitivity) and balanced TRS and XLR inputs (with +4dB sensitivity). This incredibly precise monitor weighs just 7kg.

SPECIFICATIONS

Speaker category	Studio monitor
Speaker type	Active
Max. SPL (dB; @1m)	112
Frequency range (Hz)	47 ~ 21000 (±3dB)
Frequency range (Hz)	39 ~ 25000 (-10dB)
LF transducer	1 x 6.5"
HF transducer	1 x 1"
Continuous power (W)	80
Width (mm)	222
Height (mm)	359
Depth (mm)	260
Connectors	1 x 6.3mm jack (TRS, balanced input)
Connectors	1 x RCA (Unbalanced input)
Connectors	1 x XLR (3-pin, balanced input)
Net weight (kg)	7