



ELECTRO-VOICE EVID-S5.2XB

TECHNICAL DETAILS

Speaker category	Wall speaker
Speaker type	Passive
Max. SPL (dB; @1m)	108
Frequency response (Hz)	90 ~ 20000 (-3dB)
Frequency range (Hz)	55 ~ 20000 (-10dB)
LF transducer	1 x 5.25"
HF transducer	1 x 0.75"
Nominal coverage (h/v; °)	90/90
Connectors	2 x Euroblock (4-pin)
Width (mm)	180
Height (mm)	255
Depth (mm)	148
Net weight (kg)	3.2

PRODUCT DESCRIPTION

EVID-S5.2XB is a wall-mounted, full-range, two-way loudspeaker from Electro-Voice. The column is equipped with a 5.25" woofer and a 0.75" tweeter. The equipment is constructed for operation in unconventional weather conditions (IP65).

 $Electro-Voice\ EVID-S5.2XB\ guarantees\ a\ wide\ and\ uniform\ sound\ coverage\ area\ (90^{\circ}\ horizontally)\ and\ vertically)\ with\ a\ high\ efficiency.\ With\ a\ power\ level$ of 90W, a maximum SPL of 108 dB can be achieved, and the integrated 60W transformer allows operation in 7.W/15W/30W and 60W (70V/100V) modes. The mode can be changed via a switch located on the rear panel of the speaker. Two 4-pin Euroblock terminal connectors are also located on the mentioned panel.

Thanks to the handle, it is possible to mount it on the wall and rotate the structure at an angle of 80°. The Electro-Voice EVID-S5.2XB two-way loudspeaker column, with its aesthetically design and weather-resistant construction, is an excellent choice for a wide range of surface-mount applications. The speaker is available for rental from SQM Rental House.

Product link:

https://rentalhouse.sgm.eu/gb/speakers/1427-electro-voice-evid-s52xb.html



