



CLOUD CS-S6W

TECHNICAL DETAILS

Speaker category	Wall speaker
Speaker type	Passive
Max. SPL (dB; @1m)	108
Frequency response (Hz)	90 ~ 20000 (f3)
Frequency response (Hz)	70 ~ 20000 (f10)
Impedance (②)	16
Sensitivity	91dB (1W/1m)
Sensitivity	88dB (2.83V/1m)
LF transducer	1 × 6.5"
HF transducer	1 x 1"
Connectors	1 x Euroblock (4-pin)
Width (mm)	213.5
Height (mm)	337
Depth (mm)	215.96
Net weight (kg)	3.6

PRODUCT DESCRIPTION

The Cloud CS-S6W is a coaxial two-way surface mount speaker that is suitable for both indoor and outdoor use (IP55).

The CS-S6W in white is equipped with a 6.5-inch woofer and a 1-inch tweeter. The speaker is equipped with a male 4-pin Euroblock port. Transformer taps for 100V lines are 4W/8W/16W/32W or 50W (16 ohms), and for 70V lines are 2W/4W/8W/16W/32W or 50W (16 ohms).

The speaker comes with a bracket (U-bracket) and 2 M6 threads for direct wall/surface mounting. Rent the Cloud CS-S6W speaker for your event today from SQM Rental House!

Product link:

https://rentalhouse.sqm.eu/gb/speakers/1440-cloud-cs-s6w.html



