

PRODUCT NAME

PROLIGHTS ECLEXPO FLOOD300VW

DESCRIPTION

Prolights EclExpo Flood300VW is an asymmetrical LED floodlight equipped with a 300-watt light source with a variable white color temperature between 2700 and 6500 K. The beam angle is 100° horizontally and 60° vertically. The floodlight's wide range of functionality is a response to the needs of the exhibition sector.

The EclExpo Flood300VW features excellent color rendering indexes (CRI) of 97.7 for 2700 K and 95.6 for 6500 K. The unit has an electronic dimmer from 0 to 100% with four dimming modes, as well as being equipped with a strobe function (from 1 to 30 Hz).

The unit is extremely user-friendly - the device can be remotely controlled via 5-pin DMX/RDM ports on Amphenol XLR connectors (or W-DMX (Wireless DMX) and CRMX (Lumen Radio)), as well as via knobs and control buttons on the back panel of the floodlight.

The floodlight weighs just 5.1 kg and is powered via Neutrik powerCON TRUE1 ports. Pulse width modulation (PWM) in the range of 600 ~ 25000 Hz is also possible.

The Prolights EclExpo Flood300VW LED floodlight is made for exhibition applications, and will also be perfect for showrooms. The kit includes the Prolights EclExpo Flood300VW LED floodlight, barndoor, rope

PRODUCT NAME

PROLIGHTS ECLEXPO FLOOD300VW

DESCRIPTION (CONTINUED)

sling, snap hook, clamp and power cable.

Watch the video and learn how the Prolights ExclExpo Flood300VW works. Rent it directly at SQM Rental House!

SPECIFICATIONS

Standard	RDM
Standard	DMX512
Diode type	1 x White LED
Power (W)	300
Flash frequency (min/max; Hz)	1/30
Colour rendering index (CRI)	95.6 (6500K)
Colour rendering index (CRI)	97.7 (2700K)
Colour rendering index (CRI)	94.9 (full)
Color temperature (K)	2700-6500
Dimmer (%)	0~100 (16-bit, electronic)
Beam angle (°)	60 (V)
Beam angle (°)	100 (H)
Supply voltage	100-240V AC; 50/60Hz
Max. power consumption (W)	340
Width (mm)	391
Set contains	1 x Barndoor
Set contains	1 x Wire rope sling
Set contains	Power cord
Set contains	1 x Snap hook

SPECIFICATIONS

Set contains	1 x Slim aluminium clamp
Protection Level (IP)	IP20
Height (mm)	247
Depth (mm)	210
Connectors	2 x Neutrik powerCON TRUE1 (Input/output)
Connectors	2 x Amphenol XLR (5-pin, Input/output)
Net weight (kg)	5.1