

PRODUCT NAME

PROLIGHTS ECLPROFILE CT+

DESCRIPTION

The Prolights EclProfile CT+ is an ellipsoidal profile spotlight equipped with a 96x3W Luxeon-C six-colour LED light source.

The unit allows the mixing of any colour from the RGB, Royal Blue, Mint, PC Amber palette and the selection of any colour from the RGB / CMY / HSI / XY and RAW palettes. In addition, the EclProfile CT+ offers extremely bright white light with variable temperatures from 2800 to 10000 Kelvin and advanced green correction in CCT mode!

The EclProfile CT+ spotlight is characterised by theatrical features such as tungsten lamp emulation for dimming, a virtual CTO filter (converting coloured light to tungsten), or studio features such as the aforementioned CCT green correction. The spotlight boasts excellent colour rendering indexes CRI - 97.6 for 5600 K and 93.7 for 3200 K.

With the EclProfile CT+, Prolights has also offered Gobo image projection and a linear crossfade channel from any white colour to another colour. The unit also features an electronic dimming function from 0 to 100% along with four dimmer modes, or a strobe function from 1 to 25 Hz.

The EclProfile CT+ is equipped with the high-quality EclPrl Zoom 15°-30° variable optics, which allows

PRODUCT NAME

PROLIGHTS ECLPROFILE CT+

DESCRIPTION (CONTINUED)

precise adjustment of the light beam width.

In addition to a range of fantastic features, the unit is also user-friendly - the unit can be controlled via the 5-pin DMX/RDM ports on Amphenol XLR connectors (or W-DMX (Wireless DMX) and CRMX (Lumen Radio)) or via the control panel on the rear of the unit. The spotlight additionally allows selection between four fan modes.

The EclProfile CT+ spotlight with EclPrl Zoom optics offers a wide range of applications - from TV productions, product launches, trade fairs and events such as fashion catwalks, as well as theatre and concert events.

See the Prolights EclProfile CT+ profile spotlight available at SQM Rental House in action.

SPECIFICATIONS

Standard	RDM
Standard	DMX512
Diode type	96 x Luxeon-C
Power (W)	96 x 3
Flash frequency (min/max; Hz)	1/25
Colour rendering index (CRI)	93.7 (3200K)
Colour rendering index (CRI)	97.6 (5600K)
Color temperature (K)	2800-10000
Dimmer (%)	0~100 (16-bit, electronic)
Supply voltage	100-240V AC; 50/60Hz
Max. power consumption (W)	270
Width (mm)	264
Set contains	Power cord
Set contains	1 x Snap hook
Set contains	1 x Slim aluminium clamp
Set contains	1 x EclPrl smooth filter
Set contains	1 x Barndoor
Set contains	1 x Wire rope sling
Set contains	1 x EclPrl Zoom 15°-30° lens barrel

SPECIFICATIONS

Protection Level (IP)	IP20
Height (mm)	259
Depth (mm)	539
Connectors	2 x Neutrik powerCON TRUE1 (Input/output)
Connectors	2 x Amphenol XLR (5-pin, Input/output)
Net weight (kg)	7.9