











PROLIGHTS SOLAR 27Q

TECHNICAL DETAILS

Standard	W-DMX
Standard	RDM
Standard	DMX512
Diode type	27 x RGBW / FC LEDs
Power (W)	27 x 10
Beam angle (°)	25
Luminous flux (Im)	10832
Colour rendering index (CRI)	71.8
Dimmer (%)	0~100 (16-bit, electronic)
Connectors	2 x Seetronic XLR (5-pin, Input/output)
Connectors	2 x Seetronic powerCON (Input/output)
Protection Level (IP)	IP65
Max. power consumption (W)	268
Tilt angle adjustment (°)	0/150 (manually)
Supply voltage	100-240V AC; 50/60Hz
Width (mm)	454
Height (mm)	269
Depth (mm)	83
Net weight (kg)	9
Set contains	1 x Barndoor
Set contains	1 x Wire rope sling
Set contains	Power cord
Set contains	1 x Snap hook
Set contains	1 x Slim aluminium clamp



PRODUCT DESCRIPTION

The Prolights Solar 27Q is a compact outdoor LED wash floodlight that generates a very high output of 10,832 lumens with simultaneous excellent colour mixing. The compact wash can be manually tilted in a tilt position from 0 to 150°.

The Solar 27Q floodlight is equipped with 27 RGBW LEDs each with a power of 10W, which are also combined with an optical system with magnetic asymmetric filters that can be changed very easily. The floodlight has an electronic dimmer operating from 0 to 100%.

The Solar 27Q housing is designed to dissipate heat as efficiently as possible, making the use of fans unnecessary - as a result, the unit is characterised by very quiet operation.

Hire a tailor-made compact LED wash floodlight from SQM Rental House!

Product link:

https://rentalhouse.sqm.eu/gb/lights/1511-prolights-solar-27q.html

