



ELECTRO-VOICE ZLX-15P

TECHNICAL DETAILS

| | |
|---------------------------|--------------------------------|
| Speaker category | Stage speaker |
| Speaker type | Active |
| Max. SPL (dB; @1m) | 127 |
| Frequency response (Hz) | 55 ~ 18000 (-3dB) |
| Frequency range (Hz) | 42 ~ 20000 (-10dB) |
| LF transducer | 1 x 15" EVS-15L |
| HF transducer | 1 x 1.5" DH-1K |
| Nominal coverage (h/v; °) | 90/60 |
| Peak power (W) | 1000 |
| Connectors | 1 x 3.5mm jack (Audio input) |
| Connectors | 1 x XLR (3-pin, Output) |
| Connectors | 2 x XLR/TRS Combo jack (Input) |
| Width (mm) | 423 |
| Height (mm) | 685 |
| Depth (mm) | 383 |
| Net weight (kg) | 17.3 |

PRODUCT DESCRIPTION

The Electro-Voice ZLX-15P is an active stage loudspeaker that features a 15-inch EVS-15L woofer and a 1.5-inch DH-1K tweeter. The ZLX-15P is equipped with a 1,000W class-D amplifier and a DSP processor.

The high-quality drivers provide a maximum SPL of 127 dB, and the column carries frequencies from 42 to 20000 Hz. The speaker is equipped with two symmetrical audio inputs on 1/4"-TRS/XLR combo connectors, an audio output on a three-pin XLR connector and an audio input, for example, for media players on a 3.5-millimeter jack.

The ZLX-15P's sound can be adjusted using the knobs on the rear panel (volume level, DSP control and gain control for inputs), and the LCD display allows monitoring the speaker's operation (sound level, connected inputs, preset control).

Electro-Voice ZLX-15P will also be perfect as a stage monitor - rent it from SQM Rental House!

Product link:

Rent yourself at rentalhouse.sqm.eu

© Copyright 2025 - SQM Multimedia Solutions

<https://rentalhouse.sqm.eu/gb/speakers/1590-electro-voice-zlx-15p.html>