



ELECTRO-VOICE ZLX-15P

TECHNICAL DETAILS

Speaker category	Stage speaker
Speaker type	Active
Max. SPL (dB; @1m)	127
Frequency response (Hz)	55 ~ 18000 (-3dB)
Frequency range (Hz)	42 ~ 20000 (-10dB)
LF transducer	1 x 15" EVS-15L
HF transducer	1 x 1.5" DH-1K
Nominal coverage (h/v; °)	90/60
Peak power (W)	1000
Connectors	1 x 3.5mm jack (Audio input)
Connectors	1 x XLR (3-pin, Output)
Connectors	2 x XLR/TRS Combo jack (Input)
Width (mm)	423
Height (mm)	685
Depth (mm)	383
Net weight (kg)	17.3

PRODUCT DESCRIPTION

The Electro-Voice ZLX-15P is an active stage loudspeaker that features a 15-inch EVS-15L woofer and a 1.5-inch DH-1K tweeter. The ZLX-15P is equipped with a 1,000W class-D amplifier and a DSP processor.

The high-quality drivers provide a maximum SPL of 127 dB, and the column carries frequencies from 42 to 20000 Hz. The speaker is equipped with two symmetrical audio inputs on 1/4"-TRS/XLR combo connectors, an audio output on a three-pin XLR connector and an audio input, for example, for media players on a 3.5-millimeter jack.

The ZLX-15P's sound can be adjusted using the knobs on the rear panel (volume level, DSP control and gain control for inputs), and the LCD display allows monitoring the speaker's operation (sound level, connected inputs, preset control).

Electro-Voice ZLX-15P will also be perfect as a stage monitor - rent it from SQM Rental House!

Product link:

<https://rentalhouse.sqm.eu/gb/speakers/1590-electro-voice-zlx-15p.html>