

PRODUCT NAME

P2.06 / MODULED / RIGHT CORNER

DESCRIPTION

We recommend the unique moduLED P2.06 LED screen, which is designed to work with modular frame systems used to build eco-friendly exhibition stands. This offer includes the right corner of the screen, thanks to which it is possible to create unusual shapes - corners, cubes and any other configuration at 90°.

The moduLED features excellent image quality - the pixel spacing is 2.06 mm, and the maximum brightness of 1,000 nits and HDR technology brings the image quality closer to P1 screens. The screen was constructed with True Black SMD1010 (1x1mm) and X-GOB technology, whereby the surface of the screen module is embedded in a dedicated adhesive. This results in increased resistance to damage, dust, and also contributes to effective light reflection.

The native resolution of the screen is 240x240 pixels, and viewing angles of 160° vertically and horizontally result in a fantastic quality display of the prepared content.

The moduLED's dimensions are 496x496 mm. It is fully compatible with 55 or 62 mm thick exhibition system frames.

moduLED screens are also easy to service - full front access is available, making it possible to pull out a

PRODUCT NAME

P2.06 / MODULED / RIGHT CORNER

DESCRIPTION (CONTINUED)

single module, card, or power supply without removing the entire screen.

Both the left and right corners weigh 7.5 kilograms. In contrast, the weight of the straight cabet is 8.2 kilograms. The maximum power consumption for one screen is about ~180W (~730W/m²).

Rent a moduLED screen P2.06 dedicated to modular frames at SQM Rental House and experience the true power of multimedia!

SPECIFICATIONS

Pixel pitch (mm)	2.06
Technology	MicroX X-GOB
Technology	True Black SMD1010
Cabinet width (mm)	496
Cabinet height (mm)	496
Cabinet depth (mm)	58
Resolution (px×px)	240x240
Max. power consumption per cabinet (W)	180
Viewing angles (h/v; °)	160/160
Maintenance	Front / Rear
Refresh Rate (Hz)	1920-3840
Max. brightness (cd/m²)	≥1000
Working Environment	indoor
Protection Level (IP)	IP20
Net weight (kg)	7.5