



BLACKMAGIC SDI-HDMI MINI CONVERTER

TECHNICAL DETAILS

| | |
|---------------------|--|
| Category | Converter |
| SDI compliance | SMPTE 424M-B |
| SDI compliance | SMPTE 259M |
| SDI compliance | SMPTE 372M |
| SDI compliance | SMPTE 425M |
| SDI compliance | SMPTE 292M |
| SDI compliance | SMPTE 296M |
| HDMI format support | 1080i50/59.94/60 |
| HDMI format support | 2048x1080p23.98/24/25 |
| HDMI format support | 625i25 PAL |
| HDMI format support | 720p50/59.94/60 |
| HDMI format support | 1080p23.98/24/25/29.97/30/50/59.94/60 |
| HDMI format support | 525i23.98/29.97 NTSC |
| Connectors | 1 x Mini USB-B |
| Connectors | 3 x BNC (SDI Input, Output & Alt Input) |
| Connectors | 1 x HDMI (Output) |
| Connectors | 2 x 6.3mm jack [Audio balanced output: L (Analog or digital AES/EBU) & R (Analog)] |
| Width (mm) | 114.25 |
| Height (mm) | 23 |
| Depth (mm) | 92.27 |
| Net weight (kg) | 0.198 |

PRODUCT DESCRIPTION

Rent yourself at rentalhouse.sqm.eu

© Copyright 2026 - SQM Multimedia Solutions

SQM Rental House offers a mini-converter from SDI (SD, 3G-SDI and HD) to HDMI from the American brand Blackmagic.

On one side, the device has two SDI inputs on BNC connectors (including one alternative input that is automatically switched in the case of a loss of signal by the main channel) and an SDI output that automatically matches the video input SD, HD, and 3G-SDI. In addition, a Mini-B USB connector is available to update and configure the converter.

The other side is equipped with video/audio HDMI-A output and two 6.3mm jack connectors that work as balanced analog audio (L/R) or digital AES/EBU outputs (on the left output). The maximum supported resolution is 1080p60 and 2048x1080p25. For support of 4K resolution, SQM Multimedia Support recommends BLACKMAGIC SDI-HDMI 4K MINI CONVERTER .

The mini-converter consumes approx. 5.2 watts of power and is driven by a 12-volt DC power supply.

Product link:

<https://rentalhouse.sqm.eu/gb/accessories/196-blackmagic-sdi-hdmi-mini-converter.html>