





BLACKMAGIC SDI-HDMI 4K MINI CONVERTER

TECHNICAL DETAILS

Category	Converter
SDI compliance	SMPTE 292M
SDI compliance	SMPTE 296M
SDI compliance	SMPTE 424M-B
SDI compliance	SMPTE ST-2081
SDI compliance	SMPTE 259M
SDI compliance	SMPTE 372M
SDI compliance	SMPTE 425M
HDMI format support	720p50/59.94/60
HDMI format support	1080p23.98/24/25/29.97/30/50/59.94/60
HDMI format support	625i50 PAL
HDMI format support	4K DCI p24
HDMI format support	1080i50/59.94/60
HDMI format support	525i59.94 NTSC
HDMI format support	2160p23.98/24/25/29.97/30
Connectors	3 x BNC (SDI Input, Output & Alt Input)
Connectors	1 x HDMI (Output)
Connectors	2 x 6.3mm jack [Audio balanced output: L (Analog or digital AES/EBU) & R (Analog)]
Connectors	1 x Mini USB-B
Width (mm)	114.25
Height (mm)	23
Depth (mm)	92.27







0.198 Net weight (kg)

PRODUCT DESCRIPTION

We present you with a Blackmagic converter from SDI to HDMI signal with 4K DCI resolution at 24p.

The mini-converter offers conversion from SD, HD, 3G and 6G-SDI to SD, HD, Ultra HD and 4K in HDMI. What's more, the converter allows you to send audio from SDI directly via HDMI, or via a balanced analog audio output (on a 6.3-millimeter jack) or digital AES/EBU (on the L output).

The signal is sent via the SDI (BNC) input or alternative input, which is activated when the main input loses signal. The user also has access to the Mini-B USB connector, which is used to update and configure the converter.

The device supports Full HD resolution at 60p, 3840x2160 at 30p and 4K DCI at 24p.

The Blackmagic compact converter is powered by a 12-volt DC power supply.

Product link:

https://rentalhouse.sqm.eu/gb/accessories/197-blackmagic-sdi-hdmi-4k-mini-converter.html