

PRODUCT NAME

BLACKMAGIC HDMI-SDI MINI CONVERTER

DESCRIPTION

Available at SQM Rental House Blackmagic HDMI to SDI Mini Converter is the perfect solution when there is a need to connect a device equipped with an HDMI output to a receiver with an SDI input. The compact converter allows the processing of audio/video signals from HDMI to SDI at a maximum resolution of 1920x1080 and 60p.

The device is equipped with an HDMI-A input, two SDI outputs (on BNC connectors), a Mini-B USB socket for configuring and updating the device and a power socket (12V DC).

The Blackmagic converter also offers down conversion from HD to SD. The audio signal can be sent directly from the HDMI input, as well as via the analog balanced jack inputs (6.3 millimeters) and the AES/EBU digital input (on the left jack). If you are looking for 4K resolution, SQM Rental House recommends BLACKMAGIC HDMI-SDI 4K MINI CONVERTER.

SPECIFICATIONS

Category	Converter
SDI compliance	SMPTE 424M-B
SDI compliance	ITU-R BT.656
SDI compliance	SMPTE 259M
SDI compliance	SMPTE 372M
SDI compliance	SMPTE 425M
SDI compliance	ITU-R BT.601
SDI compliance	SMPTE 292M
SDI compliance	SMPTE 296M
HDMI format support	525i23.98/29.97 NTSC
HDMI format support	1080i50/59.94/60
HDMI format support	2048x1080p23.98/24/25
HDMI format support	625i25 PAL
HDMI format support	720p50/59.94/60
HDMI format support	1080p23.98/24/25/29.97/30/50/59.94/60
Width (mm)	114.25
Height (mm)	23
Depth (mm)	92.27
Connectors	1 x Mini USB-B

SPECIFICATIONS

Connectors	2 x BNC (SDI output)
Connectors	1 x HDMI (Input)
Connectors	2 x 6.3mm jack [Audio balanced input: L (Analog or digital AES/EBU) & R (Analog)]
Net weight (kg)	0.198