





PRODUCT NAME

HIKVISION DS-D2055LU-Y 55"

DESCRIPTION

The HIKVISION DS-D2055LU-Y seamless monitor is a modern solution designed for creating impressive video walls in environments that demand high image quality. Featuring a 55-inch screen, the device offers a resolution of 1920×1080 pixels and a brightness level of 500 cd/m², providing a clear and vivid image perfect for both monitoring centers and business presentations.

This monitor features an ultra-narrow bezel with a width of 2.3 mm (top/left) and 1.2 mm (bottom/right), resulting in a combined bezel-to-bezel distance of just 3.5 mm. This allows for virtually seamless integration of multiple screens into one large display surface. The applied LED backlight technology guarantees uniform brightness across the entire screen, eliminating shadows at the edges. The monitor is factory-calibrated for color and brightness uniformity, ensuring image consistency in any environment.

The device supports 4K signal input and enables automatic daisy-chaining of up to 30 screens via HDMI interfaces, making it a flexible solution for extensive installations. Additionally, the monitor offers the ability to switch between three image modes: Monitoring, Meeting, and Movie, adapting to various usage scenarios.

Thanks to its metal housing, the monitor is resistant to radiation and electromagnetic interference,

PRODUCT NAME

HIKVISION DS-D2055LU-Y 55"

DESCRIPTION (CONTINUED)

guaranteeing stable 24/7 operation. Wall-mounting options and the availability of modular brackets make installation easy and tailored to individual user needs. Rent the HIKVISION DS-D2055LU-Y monitor at SQM Rental House.

SPECIFICATIONS

Panel	Direct LED
Diagonal (in)	55
Standard	Full HD
Resolution (px×px)	1920x1080
Width of viewable area (mm)	1209.6
Height of viewable area (mm)	680.4
Screen aspect ratio	16:9
Viewing angles (h/v; °)	178/178
VESA (mm×mm)	600x400
Max. brightness (cd/m²)	500
Width without stand (mm)	1213.7
Height without stand (mm)	684.5
Bezel width (top/left)	2.3 mm
Bezel width (bottom/right)	1.2 mm
Depth without stand (mm)	76.19
Max. power consumption (W)	245
Set contains	IR receiver
Set contains	4 x Screw
Set contains	Remote control

SPECIFICATIONS

Set contains	RJ45 - RJ45 cable
Set contains	RS232 converter
Set contains	Power cord
Set contains	HDMI - HDMI cable
Connectors	1 x DVI-I (Input, 24+5-pin D-Sub)
Connectors	2 x RS232 (Input/loop, RJ45)
Connectors	1 x VGA (Input, 15-pin D-Sub)
Connectors	1 x 3.5mm jack (Audio output)
Connectors	2 x HDMI (Input/output)
Connectors	1 x 3.5mm jack (IR)
Connectors	2 x DisplayPort (Input/output)
Connectors	1 x USB-A
Net weight (kg)	24.3