



HIKVISION DS-D2055LU-Y 55"

TECHNICAL DETAILS

Diagonal (in)	55
Panel	Direct LED
Standard	Full HD
Resolution (px×px)	1920x1080
Width of viewable area (mm)	1209.6
Height of viewable area (mm)	680.4
Screen aspect ratio	16:9
Max. brightness (cd/m ²)	500
Viewing angles (h/v; °)	178/178
Connectors	1 x DVI-I (Input, 24+5-pin D-Sub)
Connectors	2 x RS232 (Input/loop, RJ45)
Connectors	1 x VGA (Input, 15-pin D-Sub)
Connectors	1 x 3.5mm jack (Audio output)
Connectors	2 x HDMI (Input/output)
Connectors	1 x 3.5mm jack (IR)
Connectors	2 x DisplayPort (Input/output)
Connectors	1 x USB-A
Max. power consumption (W)	245
VESA (mm×mm)	600x400
Width without stand (mm)	1213.7
Height without stand (mm)	684.5
Depth without stand (mm)	76.19
Net weight (kg)	24.3
Set contains	HDMI - HDMI cable

Set contains	IR receiver
Set contains	4 x Screw
Set contains	Remote control
Set contains	RJ45 - RJ45 cable
Set contains	RS232 converter
Set contains	Power cord
Bezel width (top/left)	2.3 mm
Bezel width (bottom/right)	1.2 mm

PRODUCT DESCRIPTION

The HIKVISION DS-D2055LU-Y seamless monitor is a modern solution designed for creating impressive video walls in environments that demand high image quality. Featuring a 55-inch screen, the device offers a resolution of 1920×1080 pixels and a brightness level of 500 cd/m², providing a clear and vivid image perfect for both monitoring centers and business presentations.

This monitor features an ultra-narrow bezel with a width of 2.3 mm (top/left) and 1.2 mm (bottom/right), resulting in a combined bezel-to-bezel distance of just 3.5 mm. This allows for virtually seamless integration of multiple screens into one large display surface. The applied LED backlight technology guarantees uniform brightness across the entire screen, eliminating shadows at the edges. The monitor is factory-calibrated for color and brightness uniformity, ensuring image consistency in any environment.

The device supports 4K signal input and enables automatic daisy-chaining of up to 30 screens via HDMI interfaces, making it a flexible solution for extensive installations. Additionally, the monitor offers the ability to switch between three image modes: Monitoring, Meeting, and Movie, adapting to various usage scenarios.

Thanks to its metal housing, the monitor is resistant to radiation and electromagnetic interference, guaranteeing stable 24/7 operation. Wall-mounting options and the availability of modular brackets make installation easy and tailored to individual user needs. Rent the HIKVISION DS-D2055LU-Y monitor at SQM Rental House.

Product link:

<https://rentalhouse.sqm.eu/gb/seamless/2143-hikvision-ds-d2055lu-y-55.html>