





PRODUCT NAME

HOLLYLAND MARS 4K

DESCRIPTION

The Hollyland Mars 4K Wireless Video Transmission System is an advanced solution for professional film productions that can transmit 4K-quality video signals over distances of up to 150 meters in a straight line. With an ultra-low latency of just 0.06 seconds, the system provides smooth and virtually delay-free video transmission, which is crucial for live productions and high-quality footage.

Mars 4K is equipped with HDMI and 3G-SDI ports, providing broad compatibility with a variety of cameras, from DSLRs to professional film cameras. It also supports transmission in a variety of video formats, including UHD 4K at 30 fps and full HD and HD resolutions, allowing flexibility in the choice of parameters depending on production needs.

The system also features advanced features such as intelligent channel scanning, which automatically selects the most stable connection, and the ability to monitor live on up to four mobile devices via the Hollyview app. This is particularly useful for production teams, where several people can simultaneously follow the recording.

The construction of the Mars 4K devices is designed with durability and convenience in mind. Durable housings with corrosion-resistant components and thoughtful antenna placement ensure not only longevity, but also simplicity in setup and operation. In addition, the units can be powered in a variety of

PRODUCT NAME

HOLLYLAND MARS 4K

DESCRIPTION (CONTINUED)

ways - from NP-F batteries to DC power to USB-C charging.

The Hollyland Mars 4K is an excellent choice for anyone who needs a reliable, efficient and easy-to-use 4K video transmission system for any professional production.

Rent a set at SQM Rental House!

SPECIFICATIONS

Frequency band (GHz)	5.1 ~ 5.8
Bandwidth	20MHz
Device type	Receiver
Device type	Transmitter
Working range (m)	150
Width (mm)	65 (Transmitter/Receiver)
Set contains	1 x Carrying case
Set contains	1 x USB-C converter
Set contains	Power supply
Set contains	1 x 1/4" Cold Shoe
Height (mm)	32 (Transmitter/Receiver)
Depth (mm)	115 (Transmitter/Receiver)
Connectors	1 x USB-C (Transmitter)
Connectors	2 x Antenna (Transmitter)
Connectors	1 x HDMI (Output - Receiver)
Connectors	2 x BNC (SDI Output - Receiver)
Connectors	1 x USB-C (Receiver)
Connectors	2 x Antenna (Receiver)
Connectors	1 x HDMI (Input - Transmitter)

SPECIFICATIONS

Connectors	2 x BNC (SDI Input/Loop - Transmitter)
Net weight (kg)	0.22 (Transmitter)
Net weight (kg)	0.22 (Receiver)