





TEIL	A 4 11	
	ANK	
	-	
	_	

16	. *			-				
10		۰.	2.3			- 1	r	- 11
		2.72		-	 -	-	16.3	-

NEC NP-PA600X

TECHNICAL DETAILS

Category	Projector
Technology	0.79" LCD with MLA
Resolution (px×px)	1024x768
Contrast ratio	2000:1
Light source	1 x 330W AC
Brightness (ANSI lumens)	6000
Light source lifetime (hrs)	3000
Noise level (dB)	38
Connectors	5 x BNC (RGBHV input)
Connectors	1 x RS232 (9-pin D-Sub)
Connectors	1 x S-Video (4-pin, MiniDIN)
Connectors	1 x HDMI (Input)
Connectors	2 x RGB (Input, 15-pin D-Sub)
Connectors	1 x USB-A
Connectors	3 x Audio (Input, 3.5mm jack)
Connectors	1 x Remote (3.5mm jack)
Connectors	2 x RCA (Audio input)
Connectors	1 x Ethernet (RJ45)
Connectors	1 x RCA (Composite input)
Connectors	1 x DisplayPort (Input)
Connectors	1 x RGB (Output, 15-pin D-Sub)
Connectors	1 x Audio (Output, 3.5mm jack)
Max. power consumption (W)	464
Width (mm)	499

Rent yourself at <u>rentalhouse.sqm.eu</u>



Height (mm)	164
Depth (mm)	366
Net weight (kg)	7.7
Set contains	NEC NP12ZL lens (1.19-1.56:1)

PRODUCT DESCRIPTION

SQM Rental House proposes the NEC NP-PA600X - an LCD projector designed for many business applications. The device is equipped with a 330W AC lamp, which has a service life of 3000 hours in a standard-use mode and even 4000 hours in eco mode. The lamp emits a brightness of 6000 ANSI lumens.

The PA600X operates on a native XGA (1024x768) resolution with the maximum support of 1920x1200 (WUXGA). Thanks to advanced ECO Mode technology, it is possible to significantly extend the life of the light source and significantly reduce power consumption. PA600X also offers AutoSense technology that automates the synchronization process with a computer signal and allows for easy and quick one-touch image optimization. Thanks to the Geometric Correction Tool you can easily display the image on unusual, non-flat surfaces - without any distortion or loss of quality.

The user has at his disposal many analog and digital inputs - BNC component input, two VGA inputs, one HDMI, DisplayPort, as well as S-Video and RCA composite input. LAN and USB-A 2.0 are used as communication ports. The PA600X weighs less than 8 kilograms and works without any problems in conditions from 5 to 40°C.

Product link:

https://rentalhouse.sqm.eu/gb/projectors/24-nec-np-pa600x.html