

Pixelhue P10

TECHNICAL DETAILS



| | |
|------------------------------|--|
| Operating Modes: | Switcher / PGM only |
| Supported Video Sources | 8 bit, 10 bit, 12 bit |
| 4K Inputs/Outputs | HDMI 2.0, DP 1.2, 12G-SDI |
| Inputs | 4 x DP 1.2/HDMI 2.0, 2x 12G-SDI |
| Outputs | 2 x HDMI 2.0, 6 x HDMI 1.3 |
| AUX Outputs | allow connection of auxiliary devices, such as teleprompters |
| Dedicated Multiviewer Output | allows monitoring of PGM & PVW screens and all connected sources from a single display |
| 2 x Gigabit Ethernet Ports | used for control and monitoring |
| Number of DL Layers | Up to 6 layers (2 x 4K layers + 4 x 2K layers, or 3 x 4K layers) |
| Number of Presets | up to 128 |

PRODUCT DESCRIPTION

The Pixelhue P10 is an advanced presentation switcher supporting 4K 60p 4:4:4 10-bit video with excellent image processing. Equipped with HDMI 2.0, DP1.2, 12G-SDI, and 4 × 10G fiber ports, it can transmit signals up to 10 km without converters.

It supports both switcher mode (4K × 2K) and splicer mode (8K × 2K) with smooth transitions, effects, and flawless mosaics. It offers up to 6 layers and 128 presets, and live input/output captures can be used as backgrounds.

Control is easy and flexible via the front panel with LCD, U5 console, web GUI, or stream deck. Its robust construction ensures reliability in touring, rental, and 24/7 operation.

Product link:

<https://rentalhouse.sqm.eu/gb/strona-glowna/2615-pixelhue-p10.html>