

## OMNITRONIC C-80A



### TECHNICAL DETAILS

Speaker category	Stage speaker
Speaker type	Active
Max. SPL (dB; @1m)	N/A
Frequency range (Hz)	50 ~ 20000 (-10dB)
LF transducer	1 x 8"
HF transducer	1 x 1"
Nominal coverage (h/v; °)	N/A
Continuous power (W)	80
Peak power (W)	125
Connectors	2 x 3-pin XLR (In/Out)
Width (mm)	270
Height (mm)	360
Depth (mm)	240
Net weight (kg)	8

### PRODUCT DESCRIPTION

The C-80A is a two-way Omnitronic (Steinigke) speaker that is equipped in an 8-inch woofer and a 1-inch dome tweeter.

Omnitronic C-80A is an active speaker that works very well in the 50-20000Hz frequency range. Its efficiency measured from 1 meter at 1 watt is 90 decibels. The built-in amplifier has a continuous power of 80W, with a peak value of 125W.

The speaker user has at his disposal two balanced XLR connectors on the rear panel - input and output. The housing is made of ABS plastic and the cover is made of metal. The speaker is also equipped with a functional mounting bracket, thanks to which you can install the C-80A on the wall.

The white-color device is available in the rental SQM Rental House. C-80A is ideally suited to the PA applications.

Product link:

<https://rentalhouse.sqm.eu/gb/speakers/316-omnitronic-c-80a.html>