



## BEHRINGER EUROLIVE B212D

### TECHNICAL DETAILS

Speaker category	Stage speaker
Speaker type	Active
Max. SPL (dB; @1m)	125
Frequency range (Hz)	65 ~ 20000 (-10dB)
LF transducer	1 x 12"
HF transducer	1 x 1.35"
Nominal coverage (h/v; °)	N/A
Continuous power (W)	345 (280 LF + 65 HF)
Peak power (W)	550 (450 LF + 100 HF)
Connectors	1 x 6.3mm XLR/F (In); 1 x 6.3mm TRS (In); 1 x XLR/M (Out)
Width (mm)	345
Height (mm)	550
Depth (mm)	270
Net weight (kg)	14.5

### PRODUCT DESCRIPTION

Behringer EUROLIVE B212D is another, two-way active speaker from a wide range of speakers available at SQM Rental House. The B212D is equipped with a 12-inch low-frequency transducer that provides deep bass and an aluminum diaphragm pressure driver with a size of 1.35". The RMS power of the Behringer class D amplifier is 345W (with a ratio of 280W for the woofer and 65W for the driver), with a peak power of 550W. The maximum sound pressure level reaches 125 decibels.

B212D is equipped with an integrated sound processor. The rear panel is equipped with an XLR output and two servo-balanced inputs - 6.3mm XLR and 6.3mm TRS. The device is also equipped with an internal switching power supply, which is characterized by the great transient response. A dedicated two-band equalizer is also available to the user.

The trapezoidal shape of the housing allows B212D for both tripod and floor applications (in the form of a floor monitor speaker). High-quality components and a durable construction guarantee that Behringer B212D will not let you down in the most important moments.

Product link:

<https://rentalhouse.sqm.eu/gb/speakers/394-behringer-b212d-active-speaker.html>