





WORKPROIC811T

TECHNICAL DETAILS

Speaker category	Ceiling speaker
Speaker type	Passive
Max. SPL (dB; @1m)	104
Frequency range (Hz)	50 ~ 20000 (-10dB)
LF transducer	1 x 8"
HF transducer	1 x 0.5"
Nominal coverage (h/v; °)	N/A
Diameter (mm)	270
Depth (mm)	185
Net weight (kg)	3.1

PRODUCT DESCRIPTION

IC~811T~is~a~two-way~ceiling~speaker~from~WorkPro.~The~device~is~equipped~with~a~high-quality~8-inch~woofer~and~a~half-inch~coaxial~tweeter.

The rear panel of the speaker is equipped with a knob that allows you to quickly select the power and impedance values for 70-volt (2.5-5-10-20-40W) and 100-volt (5-10-20-40W) installations.

WorkPro IC 811T is a passive speaker that operates in the 50-20000Hz frequency range and with a nominal impedance of 82. The speaker boasts an efficiency of 88 decibels and a maximum SPL value of 104dB.

The IC 811T weighs 3.1 kilograms and requires a 240mm mounting hole. The solid housing, made of ABS plastic, safely hides a transformer and crossover underneath it. It is worth mentioning that the installation of the ceiling speaker is extremely easy - all thanks to three rotary latches.

SQM Rental House fully recommends the IC 811 T speaker.

Product link:

https://rentalhouse.sgm.eu/gb/speakers/531-workpro-ic-811-t.html

