

## WORKPRO PA 5000

### TECHNICAL DETAILS



Frequency range (Hz)	50 ~ 22000
Zones	1
Signal-to-noise ratio	≥90dB
Min. output impedance (Ω)	4
Continuous power (W)	480
Connectors	2 x 6.3mm TRS
Connectors	2 x 3-pin XLR (In/Out)
Connectors	Screw connectors (COM, 4Ω, 8Ω, 70V, 100V)
Power supply	115/230V AC; 50/60Hz
Width (mm)	483
Height (mm)	88 (2U)
Depth (mm)	400
Net weight (kg)	20

### PRODUCT DESCRIPTION

PA 5000 is a professional power amplifier of the Spanish brand WorkPro, which has an RMS output power of 480 watts. The device is capable of operating on 70- and 100-volt lines, and with low impedance speakers (4Ω and 8Ω).

The rear panel of the amplifier is equipped with a balanced XLR and 6.3-mm input. It is also possible to send the input signal via Link connectors (XLR/TRS). Above the XLR/6.3mm connectors, there is an output terminal for double (two-wire) speaker cables with low and high impedance.

The front panel offers a volume control knob and LED signal indicators. WorkPro PA 5000 is a functional amplifier - it is equipped with a three-band equalizer and an automatic signal compression function that counteracts output distortion.

The device available in the SQM Rental House is great for installations that require high output power and very good sound quality. PA 5000, whose height is equal to 2U (88mm), can be installed in a standard 19-inch rack. The maximum power consumption is 1100 watts.

Product link:

<https://rentalhouse.sqm.eu/gb/accessories/532-workpro-pa-5000.html>