


## NEC X841UHD-2 SST

### TECHNICAL DETAILS

Diagonal (in)	84
Panel	S-IPS
Touch points	10
Standard	UHD 4K
Resolution (px×px)	3840x2160
Width of viewable area (mm)	1860.5
Height of viewable area (mm)	1046.5
Upper / lower bezel size (mm)	35.25 / 35.25
Left / right bezel size (mm)	35.25 / 35.25
Max. brightness (cd/m <sup>2</sup> )	500
Viewing angles (h/v; °)	178/178
Connectors	2 x DVI-D (Input, 24+1-pin D-Sub)
Connectors	2 x USB-A
Connectors	1 x RS-232C (9-pin D-Sub)
Connectors	4 x HDMI (Input)
Connectors	2 x 3.5mm jack (Line input/output)
Connectors	Spring clip output terminal (Speakers)
Connectors	1 x Remote (3.5mm jack)
Connectors	1 x DisplayPort (Input)
Connectors	1 x USB-B
Connectors	2 x Ethernet (RJ45)
Max. power consumption (W)	512
Width without stand (mm)	2000
Height without stand (mm)	1194



Depth without stand (mm)	105
Net weight (kg)	110
Set contains	Power cord
Set contains	Edbak PWB1 wall mount
Set contains	Remote control

## PRODUCT DESCRIPTION

NEC X841UHD-2 SST is a large-format, 84-inch touch screen monitor that supports 4K UHD 3840x2160 resolution. The monitor uses the innovative ShadowSense multiple touch technology, which allows the simultaneous operation of ten touchpoints. It is based on optical position detection, thanks to perfectly calibrated sensors. This makes the X841UHD-2 SST monitor an incredibly accurate, efficient and stable device.

The NEC SpectraView engine delivers amazing, full of detail 4K resolution and a palette of vivid colors. The ZG technology ensures that the parallax error is eliminated. Thanks to specially tailored and efficient filtering, it is possible to ensure error-free and interference-free operation of the monitor in high-intensity lighting. The device operates at brightness up to 500 cd/m<sup>2</sup>

The X841UHD-2 SST is a plug&play type of monitor, which makes it possible to connect an additional slot-in device with ultra-high resolution without the need for additional drivers. The TV has a full range of digital inputs: four HDMI connectors, two DVI-D and one DisplayPort.

The monitor is ideal for interactive applications that require intensive usage for 24 hours, seven days a week. It is worth noting that the monitor weighs 110kg (without stand) - therefore a reinforced wall and additional installation assistance are required. The spacing of mounting holes (M8) in the VESA standard is 400x400mm.

Product link:

<https://rentalhouse.sqm.eu/gb/touch-monitors/559-nec-x841uhd-2-sst.html>