



## DAS VANTEC 15A

### TECHNICAL DETAILS

Speaker category	Stage speaker
Speaker type	Active
Max. SPL (dB; @1m)	135
Frequency range (Hz)	45 ~ 20000 (-10dB)
LF transducer	1 x 15" 15FV4
HF transducer	1 x 1" M-28
Nominal coverage (h/v; °)	90/50
Continuous power (W)	750
Peak power (W)	1500
Connectors	2 x Combo XLR/F (In); 1 x 3.5mm jack (In); 1 x XLR/M (Out)
Width (mm)	380
Height (mm)	720
Depth (mm)	380
Net weight (kg)	24

### PRODUCT DESCRIPTION

The Vantec 15A is a two-way active column from the DAS, which is defined by a class D amplifier with a peak power of 1500W and an RMS power of 750W. Vantec 15A is one of the leading items from the wide range of SQM Rental House mobile sound system, which guarantees extremely low sound distortion.

The maximum value of the sound pressure level is 135dB, and the angle of sound dispersion is 90° horizontally and 50° vertically. The speaker has a 15-inch 15FV4 woofer, which is responsible for playing low frequencies, and a 1-inch M-28 HF transducer.

The Vantec 15A is equipped with a 24-bit DSP processor, three-band equalizer, and functional presets such as Live, Dance, Vocal, Bass Boost and Monitor. A useful function of the device is an automatic switch to standby when no signal is supplied to the column - the time parameter can be set via the DSP menu. Everything is complemented by the option of playing music from mobile devices via a wireless network.

The rear panel of the column is equipped with a powerCON power slot, two 6.3mm Combo XLR inputs, and a 3.5mm AUX input. Two input channels also have a signal regulator. The Vantec 15A has one XLR output, which is mainly intended for serial connection of columns. To hang the column, the user has M10 sockets at its disposal.

Product link:

<https://rentalhouse.sqm.eu/gb/speakers/637-das-vantec-15a-active-speaker.html>