



## SHOWTEC COMPACT PAR 7 Q4

### TECHNICAL DETAILS

Standard	DMX512
Diode type	7 x RGBW LED
Power (W)	7 diodes x 4
Beam angle (°)	18
Flash frequency (min/max; Hz)	1/20
Protection Level (IP)	IP20
Max. power consumption (W)	32
Supply voltage	100-240V AC; 50/60Hz
Width (mm)	92
Height (mm)	260
Depth (mm)	272
Net weight (kg)	2.14

### PRODUCT DESCRIPTION

The Compact Par 7 Q4 is a Showtec reflector, which is equipped with 7 LED 4-in-1 lamps in the RGBW color system, which allows the reproduction of fantastic, vivid colors. The beam angle is 18 degrees. The device offers the user 6 modes of operation:

Built-in Programs mode , which reproduces previously saved lighting parameters; Auto mode in which the remembered configuration is automatically played; Sound control mode in which the lighting effects are changed depending on the rhythm of the music; Static color mode in which a static color is constantly played; Master/Slave mode , in which it is possible to connect other devices with the Daisy chain. They synchronize with the first device plugged into the line and reproduce the parameters assigned to it; DMX mode in which you can control the device from the console position (DMX512 standard).

Compact Par 7 Q4 offers support for 4, 6 and 11 DMX channels. It is possible to dim the light from 0 to 100% and enable the strobe effect in the frequency range from 0 to 20 Hz. The user can also control the reflector through a 4-button LED display, which is located on the rear panel of the housing. The IEC connector and 3-pin XLR input/output (DMX) are located on the upper panel of the housing. The compact dimensions of the reflector and the weight of 2.14kg allow for easy transport and assembly anywhere on the stage.

Product link:

<https://rentalhouse.sqm.eu/gb/lights/649-showtec-compact-par-7-q4.html>