








IIYAMA TF4938UHSC-B1AG

TECHNICAL DETAILS

Diagonal (in) 49 Panel IPS Touch points 12 Standard UHD 4K Resolution (pxxpx) 3840x2160 Width of viewable area (mm) 1073.8 Height of viewable area (mm) 604 Upper / lower bezel size (mm) 40.140.1 Screen aspect ratio 16:9 Max. brightness (cd/m²) 420 Viewing angles (h/v;°) 178/178 Connectors 1 x USB-B Connectors 1 x IR (3.5mm jack) Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Connectors 1 x DVGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm) 1154 Height without stand (mm) 684		
Touch points 12 Standard UHD 4K Resolution (px×px) 3840x2160 Width of viewable area (mm) 1073.8 Height of viewable area (mm) 604 Upper / lower bezel size (mm) 40.140.1 Screen aspect ratio 16:9 Max. brightness (cd/m²) 420 Viewing angles (h/v; °) 178/178 Connectors 1 x USB-B Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 2 x HDMI (Input) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Connectors 1 x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm) 1154	Diagonal (in)	49
Standard UHD 4K Resolution (px×px) 3840x2160 Width of viewable area (mm) 1073.8 Height of viewable area (mm) 604 Upper / lower bezel size (mm) 40.140.1 Screen aspect ratio 16.9 Max. brightness (cd/m²) 420 Viewing angles (h/v; °) 178/178 Connectors 1 x USB-B Connectors 1 x IR (3.5mm jack) Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Connectors 1 x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm) 1154	Panel	IPS
Resolution (px×px) 3840x2160 Width of viewable area (mm) 1073.8 Height of viewable area (mm) 604 Upper / lower bezel size (mm) 40.1/40.1 Screen aspect ratio 16:9 Max. brightness (cd/m²) 420 Viewing angles (h/v; °) 178/178 Connectors 1 x USB-B Connectors 1 x IR (3.5mm jack) Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm) 1154	Touch points	12
Width of viewable area (mm) Height of viewable area (mm) Upper / lower bezel size (mm) Left / right bezel size (mm) Au.1 / 40.1 Screen aspect ratio 16.9 Max. brightness (cd/m²) Viewing angles (h/v; °) 178/178 Connectors 1 x USB-B Connectors 1 x IR (3.5mm jack) Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm) 1154	Standard	UHD 4K
Height of viewable area (mm) Upper / lower bezel size (mm) Left / right bezel size (mm) Left / right bezel size (mm) 40.1/40.1 Screen aspect ratio 16:9 Max. brightness (cd/m²) 420 Viewing angles (h/v; °) 178/178 Connectors 1 x USB-B Connectors 1 x IR (3.5mm jack) Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x DisplayPort (Input) Connectors 1 x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm) 1154	Resolution (px×px)	3840x2160
Upper / lower bezel size (mm)40/40Left / right bezel size (mm)40.1/40.1Screen aspect ratio16:9Max. brightness (cd/m²)420Viewing angles (h/v; °)178/178Connectors1 x USB-BConnectors1 x IR (3.5mm jack)Connectors2 x Audio (Input/output, 3.5mm jack)Connectors2 x HDMI (Input)Connectors1 x RS-232C (9-pin D-Sub)Connectors1 x DVI-D (Input, 24+1-pin D-Sub)Connectors1 x Ethernet (RJ45)Connectors1 x DisplayPort (Input)Connectors1 x VGA (Input, 15-pin D-Sub)Max. power consumption (W)115Width without stand (mm)1154	Width of viewable area (mm)	1073.8
Left / right bezel size (mm) Screen aspect ratio 16:9 Max. brightness (cd/m²) Viewing angles (h/v; °) 178/178 Connectors 1 x USB-B Connectors 1 x IR (3.5mm jack) Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm) 16:9 40.1/40.1 40.1 40.1 40.1 40.1 420 420 178/178 420 178/178 1x USB-B 1 x USB-B 1 x IR (3.5mm jack) 1	Height of viewable area (mm)	604
Screen aspect ratio Max. brightness (cd/m²) Viewing angles (h/v; °) 178/178 Connectors 1 x USB-B Connectors 1 x IR (3.5mm jack) Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 2 x HDMI (Input) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x DisplayPort (Input) Connectors 1 x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm)	Upper / lower bezel size (mm)	40 / 40
Max. brightness (cd/m²)420Viewing angles (h/v; °)178/178Connectors1 x USB-BConnectors1 x IR (3.5mm jack)Connectors2 x Audio (Input/output, 3.5mm jack)Connectors2 x HDMI (Input)Connectors1 x RS-232C (9-pin D-Sub)Connectors1 x DVI-D (Input, 24+1-pin D-Sub)Connectors1 x Ethernet (RJ45)Connectors1 x DisplayPort (Input)Connectors1 x VGA (Input, 15-pin D-Sub)Max. power consumption (W)115Width without stand (mm)1154	Left / right bezel size (mm)	40.1 / 40.1
Viewing angles (h/v; °) Connectors 1x USB-B Connectors 1x IR (3.5mm jack) Connectors 2x Audio (Input/output, 3.5mm jack) Connectors 2x HDMI (Input) Connectors 1x RS-232C (9-pin D-Sub) Connectors 1x DVI-D (Input, 24+1-pin D-Sub) Connectors 1x Ethernet (RJ45) Connectors 1x DisplayPort (Input) Connectors 1x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm)	Screen aspect ratio	16:9
Connectors 1 x USB-B Connectors 1 x IR (3.5mm jack) Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 2 x HDMI (Input) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x DisplayPort (Input) Connectors 1 x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm) 1154	Max. brightness (cd/m²)	420
Connectors 1x IR (3.5mm jack) Connectors 2x Audio (Input/output, 3.5mm jack) Connectors 1x RS-232C (9-pin D-Sub) Connectors 1x DVI-D (Input, 24+1-pin D-Sub) Connectors 1x Ethernet (RJ45) Connectors 1x DisplayPort (Input) Connectors 1x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm) 1154	Viewing angles (h/v; °)	178/178
Connectors 2 x Audio (Input/output, 3.5mm jack) Connectors 2 x HDMI (Input) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm) 1154	Connectors	1 x USB-B
Connectors 2 x HDMI (Input) Connectors 1 x RS-232C (9-pin D-Sub) Connectors 1 x DVI-D (Input, 24+1-pin D-Sub) Connectors 1 x Ethernet (RJ45) Connectors 1 x DisplayPort (Input) Connectors 1 x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm) 1154	Connectors	1 x IR (3.5mm jack)
Connectors 1x RS-232C (9-pin D-Sub) Connectors 1x DVI-D (Input, 24+1-pin D-Sub) Connectors 1x Ethernet (RJ45) Connectors 1x DisplayPort (Input) Connectors 1x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm) 1154	Connectors	2 x Audio (Input/output, 3.5mm jack)
Connectors 1x DVI-D (Input, 24+1-pin D-Sub) Connectors 1x Ethernet (RJ45) Connectors 1x DisplayPort (Input) Connectors 1x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm) 1154	Connectors	2 x HDMI (Input)
Connectors 1x Ethernet (RJ45) Connectors 1x DisplayPort (Input) Connectors 1x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm) 1154	Connectors	1 x RS-232C (9-pin D-Sub)
Connectors 1 x DisplayPort (Input) Connectors 1 x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm) 1154	Connectors	1 x DVI-D (Input, 24+1-pin D-Sub)
Connectors 1 x VGA (Input, 15-pin D-Sub) Max. power consumption (W) 115 Width without stand (mm) 1154	Connectors	1 x Ethernet (RJ45)
Max. power consumption (W) 115 Width without stand (mm) 1154	Connectors	1 x DisplayPort (Input)
Width without stand (mm) 1154	Connectors	1 x VGA (Input, 15-pin D-Sub)
	Max. power consumption (W)	115
Height without stand (mm) 684	Width without stand (mm)	1154
	Height without stand (mm)	684







Depth without stand (mm)	73.5
Net weight (kg)	30
Set contains	Remote control
Set contains	Power cord
Set contains	Vogel's PFW 4500 wall mount

PRODUCT DESCRIPTION

liyama TF4938UHSC-B1AG is a 3840x2160 Ultra HD touch screen monitor. TF4938UHSC-B1AG with a 49-inch screen has an anti-glare coating and uses an IPS matrix - all this means that the liyama monitor has a picture full of vivid colors with great contrast, with a wide viewing angle and, above all, in amazing UHD quality.

The device supports up to 12 touchpoints. For this, it uses capacitive technology - when a finger is placed on the glass, the device detects touch because of the electrical characteristics of the sensor grid change. The 4mm thick glass coating is very durable, scratch-resistant and HID-compliant. In addition, the housing is uniform and smooth, and the bezels don't obstruct the screen.

TF4938UHSC-B1AG has three types of digital video inputs - two HDMI 1.4 and one DisplayPort and DVI. The monitor is equipped with two built-in 8W speakers and works great in both horizontal and vertical orientation.

The TF4938UHSC-B1AG offered by SQM Rental House is an liyama monitor from the open-frame series, which can be mounted on the wall through 600x400mm slots in VESA standard. It is a great solution as an interactive kiosk at points of sale or as an interactive, commercial screen. The monitor is capable of working 24/7.

Product link:

https://rentalhouse.sqm.eu/gb/touch-monitors/902-iiyama-tf4938uhsc-b1ag.html