





PRODUCT NAME

FLASH PROFESSIONAL PAR (250W)

DESCRIPTION

The 250W PAR spotlight from the Flash Professional series is a device characterized by its durability, modern design and a wide range of lighting effects.

The reflector has a light source that its color temperature can be regulated from warm white (2,200 Kelvin) to a natural white (5,200 Kelvin) temperature.

Thanks to the brightness control through two DMX512 channels, the reflector achieves over 65,000 brightness levels. Thanks to the Dim Delay function, it is also possible to smoothly dim - this is done by the delayed reaction of the LEDs on the value change on the DIMMER channel.

Flash LED PAR has the following operating modes:

Auto mode, thanks to which it works independently, implementing the set parameters; Sound control mode, thanks to which the headlight synchronizes its operation with the sound; Master/Slave mode, thanks to which the other PARs connected via DMX synchronize their work with the first, connected device; DMX512 mode, thanks to which you can control the equipment via external consoles.

The device offers nine DMX control modes, as well as RGB and RGBW modes. The Flash LED PAR gives

PRODUCT NAME

FLASH PROFESSIONAL PAR (250W)

DESCRIPTION (CONTINUED)

the possibility of smooth dimming from 0 to 100% and a flash with a frequency of 1 to 20 Hz.

The user has at their disposal a 1.8-inch LCD screen with four buttons, which allows for very comfortable control of the device functions. The equipment is intended for both professionals and people using only basic functions. The spotlight is perfect for the organization of professional television and stage installations.

SPECIFICATIONS

Standard	DMX512
Diode type	2 x White COB
Power (W)	250
Flash frequency (min/max; Hz)	1/20
Color temperature (K)	2200-5200
Beam angle (°)	37
Supply voltage	100-245V AC; 50/60Hz
Max. power consumption (W)	250
Width (mm)	270
Protection Level (IP)	IP20
Height (mm)	280
Set contains	1 x Shackle 0.5T
Set contains	1 x Clamp 50mm/100kg
Set contains	1 x Safety rope 1m/10kg
Net weight (kg)	3.4
Depth (mm)	240