



BEHRINGER XENYX 1002

TECHNICAL DETAILS

Mixer category	Audio
Mixer type	Analog
Channels	4 (Stereo, line)
Channels	2 (Mono, mic/line)
Frequency response (Hz)	10 ~ 200000 (-3dB)
Frequency response (Hz)	10 ~ 150000 (-1dB)
THD+n (%)	0.005 (A-weighted)
Headroom (dB)	N/A
Connectors	2 x 6.3mm jack (Main unbalanced output)
Connectors	2 x 6.3mm TRS (Line balanced input)
Connectors	8 x 6.3mm TRS (Stereo balanced input)
Connectors	2 x XLR (3-pin, Mic balanced input)
Connectors	4 x RCA (2-Track, In/out)
Connectors	4 x 6.3mm jack (Phones TRS, FX, Control Room Out TS)
Power supply	230V AC; 50Hz
Width (mm)	189
Height (mm)	47
Depth (mm)	220
Net weight (kg)	1.6

PRODUCT DESCRIPTION

Behringer Xenyx 1002 is a 10-channel analog mixer, which is equipped with Xenyx microphone preamplifiers (XLR 3-pin female connectors) and a three-band equalizer.

The compact mixer also has plenty of 6.3 mm jack inputs - two mono balanced line inputs, eight stereo TRS connectors for line channels (3/4, 5/6, 7/8 and 9/10), as well as signal outputs for sending sums to foldbacks (TS). There is also a headphone connector, effects processor connector, and Main output. Additional stereo inputs and outputs (L/R, 2-Track) are also available on the left.

The lower panel contains a three-band equalizer with a constant value for high (12kHz), medium (2.5kHz) and low (80Hz) frequencies with the possibility of +/-15dB correction. Below them, there is a low-cut button that suppresses low sounds, FX knob that controls the signal output, panorama adjuster and an adjuster for the signal level of a particular channel.

The right side has i.a. signal volume fader for unbalanced outputs and a phantom power switch (48V) for condenser microphones.

The Behringer Xenyx 1002 mixer available at SQM Rental House is the perfect stage equipment.

Product link:

<https://rentalhouse.sqm.eu/gb/audio-mixers/998-behringer-xenyx-1002.html>