

OMNITRONIC C-50A (BLACK)



TECHNICAL DETAILS

Speaker category	Wall speaker
Speaker type	Active
Max. SPL (dB; @1m)	N/A
Frequency range (Hz)	50 ~ 20000 (-10dB)
LF transducer	1 x 5"
HF transducer	1 x 1"
Nominal coverage (h/v; °)	N/A
Continuous power (W)	50
Peak power (W)	80
Connectors	2 x 3-pin XLR (In/Out)
Width (mm)	180
Height (mm)	230
Depth (mm)	166
Net weight (kg)	3

PRODUCT DESCRIPTION

Omnitronic C-50A is a two-way active loudspeaker in a black version, whose 5-inch woofer and 1-inch tweeter are driven by a built-in amplifier. It offers continuous power of 50 watts, and the maximum value (peak) reaches 80W.

Omnitronic C-50A is a device that operates in the 50-20000Hz frequency range. Speaker efficiency, which is measured in the main axis of the device from 1 meter and a power of 1 watt, is equal to 89 decibels. Great parameters of the C-50A and its functional mounting bracket, thanks to which you can place the speaker on a wall or ceiling, makes it a perfect for PA applications.

The C-50A speaker is equipped with a 3-pin XLR input and output, which are located above the IEC power connector on the rear panel. The housing of the 3-kilo speaker is made of ABS plastic, and its protective grill is made of metal.

SQM Rental House also proposes an Omnitronic C-50A speaker in white color.

Product link:

<https://rentalhouse.sqm.eu/gb/sound/121-omnitronic-c-50a-black.html>