



OMNITRONIC C-50A (WHITE)

TECHNICAL DETAILS

Speaker category	Wall speaker
Speaker type	Active
Max. SPL (dB; @1m)	N/A
Frequency range (Hz)	50 ~ 20000 (-10dB)
LF transducer	1 x 5"
HF transducer	1 x 1"
Nominal coverage (h/v; °)	N/A
Continuous power (W)	50
Peak power (W)	80
Connectors	2 x 3-pin XLR (In/Out)
Width (mm)	180
Height (mm)	230
Depth (mm)	166
Net weight (kg)	3

PRODUCT DESCRIPTION

SQM Rental House offers the Omnitronic C-50A active speaker in white color. The two-way loudspeaker is equipped with a 5-inch low-frequency transducer and a 1-inch dome tweeter. The rear speaker panel offers balanced XLR input and output with three pins.

The C-50A perfectly reproduces the frequencies in the range from 50 Hz to 20 kHz, and its efficiency is 89 decibels (measured on the main axis from 1 meter and at 1 watt). The built-in amplifier operates at a continuous power of 50W, and the peak power parameter is 80W.

The solid Omnitronic C-50A loudspeaker housing is made of ABS plastic, while the protective grill is made of metal. Thanks to the movable and functional mounting bracket, the user can install the speaker on the wall. One speaker weighs 3 kilograms.

SQM Multimedia Support also offers you the C-50A speaker in a black version.

Product link:

<https://rentalhouse.sqm.eu/gb/sound/96-omnitronic-c-50a-white.html>